

Endura RP32USE



SPECIFICATIONS:

FEATURES:

- Fashionable design
- Top paper loading
- Front exit
- High printing speed up to 260mm/s
- 2" & 3" printing paper widths available
- Versatile interfaces: USB, Serial, Ethernet, Bluetooth, Wi-Fi, Cashdrawer
- Provide Windows, Linux, POSReady, OPOS driver
- SDK for iOS, Android & Windows

ITEM	PARAMETER	
Printing	Print Method	Direct Thermal Line Printing
	Resolution	Standard 203dpi (8dots/mm) Emulated 180dpi (7dots/mm)
	Print Speed	Max. 260mm/s
	Printing Width	72mm
Interface	Standard	USB+Serial+Ethernet
	Optional	Bluetooth or Wi-Fi
Page Mode		Support
Memory	RAM	32 MB
	ROM	16 MB
Fonts	Chinese	GBK 24x24 dots
	Alphanumeric	ASCII 9x17, 12x12 dots
	User-defined	Yes
	Codepage	48
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODEBAR, CODE128, CODE93
	2D	PDF417, QR Code
Graphics		Support bitmap printing with different density and user defined bitmap printing (Max size of each bitmap is 64K, the total size of bitmap is 256k)
Detections Reliability	Sensors	Paper out paper near end sensors, cover open switch
	TPH life Cutter life	150km 2 million cuts
Power Supply	Input	AC 100V 240V
	Output	DC 24V/2.5A
Paper	Paper Type	Thermal Receipt Paper
	Paper Width	58mm/80mm
	Paper Thickness	0.056~0.1mm
	Roll Paper Diameter	Max. OD dp 83mm
	Paper Load	Easy paper loading
	Paper Cut	Partial cut or full cut
Environment	Operation	0°C~45°C, 25%~85%RH
		-30°C~60°C, 5%~95%RH
Physical Characteristics	Dimension	165(L)x130(W)x119(H)mm
	Weight	1.35KC (Without paper Roll)
Options & Accessories		USB/Serial Cable, Paper Roll Power Adapter, Power Cord, CD, Quick Start Guide
Software	Emulation Driver	ESC/POS Windows 2000 / XP / Win / Win8 / Win 10 / POSReady / Linux / OPOS / JavaPOS
	SDK	WinCE, Win Mobile, Android, iOS



Fast Speed



Easy Loading



Windows



OPOS